

AMENDMENTS TO THE SPECIFICATION

Page 5, seventh and eighth paragraphs, please amend as follows; and add the following new paragraph following the eighth paragraph:

Fig. 4 is a side view showing the connector cover; ~~and~~

Fig. 5 is a rear view showing the connector cover; and

Figs. 6A and 6B are side and front views, respectively, of the connecting structure.

Page 8, first full paragraph, please amend as follows:

In the first and second mounting parts 11, 13, guide rails 14 extending in a longitudinal direction of the connector part 3 are respectively provided. The connector cover 9 is adapted to be supported (mounted) by these guide rails 14 in such a manner that the connector cover 9 can slidably move between a locked position shown in Figs. 6A and 6B, and an unlocked position, shown in Figs. 1 and 2. The locked position is a position in which the connector cover 9 is engaged with the specified connector 8 which has been engaged and connected with the connector part 2 in order to prevent the specified connector 8 from disconnecting therefrom. The unlocked position is a position in which connection of the specified connector 8 to the connector part 2 can be performed, and more preferably, the position in which connection of another connector to the connector part 3 cannot be performed.

Page 14, third paragraph, please amend as follows:

Amendment Under 37 C.F.R. § 1.111
Serial No. 10/608,231
Sughrue Ref: Q76187

Further, when the connector cover 9 is positioned in the locked position, the cover portion 15 serves as a partition for separating the connector part 2 from the connector part 3, as shown in Fig. 6B. As the results, it will be easy to connect the other connector to the connector part 3, and the connection can be reliably performed.